

How to achieve this in WordPress?

- Main Product page (1) that lists Product Families
 - Next level is individual Product Family page (2) that lists all the products that make up a Family
 - Third level is the individual Product Page (3)
- Our goal is to have the user enter the data once via fields on the Product page and have that flow to the Family and Main product pages.
- The other question is how to get the fields on the Main Product page and the Family page to loop?

Products | Reqs/Distributors | Knowledge Base | Literature | Projects | About | Contact Us | Search

EMSEAL LIVE CHAT OFFLINE

Products: Building Expansion Joints and Sealants

Selection Guides: Walls | Decks | Split Slab | Stadium | Fire-Rated | Roofs | Below-Grade | Immersed | Interior

Order/Inquiry Checklist

WALL SYSTEMS

COLORSEAL-ON-A-REEL

SEISMIC COLORSEAL

SEISMIC COLORSEAL-DS

EMSHIELD WFR2 and WFR3

EMSHIELD SecuritySeal SSF2 and SSF3

BACKERSEAL

DECKS SOLID SLAB

COLORSEAL-ON-A-REEL

DSM SYSTEM

S2S SYSTEM

EMSHIELD DFR2 and DFR3

EMSHIELD S2S-FR1 and S2S-FR2

EMSHIELD SecuritySeal SSF2 and SSF3

HORIZONTAL COLORSEAL

THERMALFOX

EMCRETE

DECKS SPLIT SLAB

MIGUTAN FP-Series

DSM FP SYSTEM

EMSHIELD DFR FP SYSTEM

S2S FP SYSTEM

EMSHIELD S2S-FP-FR2 SYSTEM

EMSHIELD FIRE-RATED

EMSHIELD WFR2 and WFR3

EMSHIELD SecuritySeal SSW2

EMSHIELD DFR2 and DFR3

EMSHIELD DFR FP SYSTEM

EMSHIELD S2S-FR1 and S2S-FR2

EMSHIELD SecuritySeal SSF2 and SSF3

EMSHIELD S2S-FP-FR2 SYSTEM

Main Product Page (1)

Products | Reqs/Distributors | Knowledge Base | Literature | Projects | About | Contact Us | Search

EMSEAL LIVE CHAT OFFLINE

Wall Joints Above-Grade--Selection Guide:

Selection Guides: Walls | Decks | Split Slab | Stadium | Fire-Rated | Roofs | Below-Grade | Immersed | Interior

Product Image	Product	Features	Joint Size
	SEISMIC COLORSEAL	• 100% Movement (+/-50%) • Primary Seal	1/2" to 1 1/2" (13 - 38mm)
	COLORSEAL-ON-A-REEL	• 90% Movement (+/-50%) • Primary seal • Smooth convex surface • Low cost • Rapid install alternate	
	SEISMIC COLORSEAL DS (Double Sided)	• 100% Movement (+/-50%) • Silicone coated on both sides of sealant	

Family Page (2)

Products | Reqs/Distributors | Knowledge Base | Literature | Projects | About | Contact Us | Search

EMSEAL LIVE CHAT OFFLINE

SEISMIC COLORSEAL

Silicone-coated, pre-compressed, primary seal in high-movement, vertical-plane wall joints in virtually any substrate.

Tech Data | Install Data | MSDS | Guide Spec | EAD | Sample | Projects | Checklist | *en español*

SEISMIC COLORSEAL by EMSEAL
Highly elastic, durable and long-lasting

Features

- Primary seal
- Watertight
- Durable
- Insulates
- Sound attenuation
- AUSA Compliant
- Resists hurricane force wind & water
- Tensionless silicone bellows
- Rapid installation—new or retrofit
- Non-invasive anchoring
- Aesthetically and practically versatile
- Easily handles changes in plane and direction
- Easily handles curved expansion joints
- 100% free of wax compounds (*why does this matter?*)

Uses

- Curtainwall
- Roofs
- Precast
- Metal panel
- Natural Stone
- EIFS, etc.

Standard Sizes

- 1/2" to 1 1/2" (13mm - 38mm)

Note: Sizes under 1 1/2" (40mm) are manufactured with a single bellows. Larger sizes incorporate multiple bellows.

Movement Capability

- Total 100% (+50% and -50%) of nominal supplied size.

Colors

- 28 Standard COLORS
- Custom Colors

Individual Product Page (3)